

Supakwik water heaters

Instant boiling water on demand

Made in Australia





Features

- **Fully Automatic**, wall mounted instant boiling water dispenser.
- **"SUPASILENT' Standby Operation** quietly maintains water at boiling point ready for immediate use.
- **Element Power Management** conserves energy by progressively reducing power to the element when approaching boiling point preventing the generation of energy sapping steam.
- **Energy Efficient** the storage vessel has the smallest surface area to water ratio reducing heat loss.
- **Simple & Reliable** designed with minimum moving parts, proven components & quality materials, manufactured and assembled to precise standards ensures performance and longevity.
- **Triple Safety Feature** Supakwik products incorporate electronic temperature management which ensures that the product does not overheat. The appliance will not be damaged by switching on the appliance without a water supply or if the water supply is accidently interrupted. When supply returns, the heater will automatically begin operating normally. Furthermore, the heating element has an independent safety device to protect against abnormal operation
- **Warranty** the Kwikboil range is covered by a comprehensive warranty with a 3 year warranty on the storage vessel.
- Optional Extras A safety tap, filtration and tun dishes are available as optional extras.

Model Selection Guide

| Model | Initial Delivery cups at one time | | Nominal Capacity | Recovery cups/min | | Element Rating | Dimensions | | Weight Kg | |
|--------|-----------------------------------|-------|---------------------|--------------------------|-------|-------------------|-------------------------|------|--------------|--|
| | 167ml | 200ml | (litres) | 167 ml | 200ml | (kW) | $(H \times W \times D)$ | dry | full | |
| SA0204 | 20 | 15 | 3 | 2.5 | 2 | 2.4 | 372 x 260 x 155 | 5.5 | 8.6 | |
| SA0384 | 38 | 30 | 6 | 2.5 | 2 | 2.4 | 422 x 312 x 170 | 7.2 | 14.8 | |
| SA0504 | 50 | 40 | 8 | 2.5 | 2 | 2.4 | 512 x 312 x 170 | 8.1 | 17.2 | |
| SA0754 | 75 | 60 | 12 | 2.5 | 2 | 2.4 | 517 x 340 x 205 | 9.3 | 23.0 | |
| SA1004 | 100 | 80 | 16 | 2.5 | 2 | 2.4 | 547 x 365 x 218 | 11.0 | 28.8 | |
| SA1604 | 160 | 138 | 25 | 2.5 | 2 | 2.4 | 550 x 415 x 265 | 12.3 | 37.8 | |

Technical Specification

Controls Electrical Supply Rating: Electrical Connection: Water Supply Pressure:

Water Supply Connection:

Full Electronic 10 Amps @ 240 VAC 10 Amp 3 pin plug 20 kPa minimum 1000 kPa maximum ½" BSP All Supakwik products are manufactured under an independently audited certified quality system.

All products are tested and comply with relevant Australian Standards including AS3498, AS4020, AS/NZS60335-2-15, AS/NZS1044 & AS/NZS4417.

As the company policy is that of continual improvement, all detail and specifications are subject to change without notice.





Supakwik Water Heaters Pty Ltd 61 Boyland Avenue, Coopers Plains QLD 4108

Telephone +61 7 3255 6389 Facsimile +61 7 3255 6387

Website www.supakwik.com.au