

# Zip HydroTap<sup>®</sup> G4

Chilled | Filtered | Instantly

**Commercial models C 125 G4, C 175 G4**

With new Zip G4 power-saving technology and Zip 0.2 micron filtration.



Simple to install on any kitchen sink.



New under-bench Zip Command Centre™ leads the world in time-saving and energy-saving technology, reducing standby energy consumption substantially over earlier models of similar capacity.

## Typical Specification

“Under-bench chilled filtered water appliance equipped with integral 500 kPa pressure limiting and dual check valve, 0.2 micron water filter, air cooled refrigeration system with cleanable lint filter, an interactive touch screen display with password protection.”



Can be installed away from any sink with the optional 'font' kit accessory.

**Chilled filtered drinking water always on tap from a new, space-saving Command Centre.**

**Adjustable chilled water temperature:** 5°C to 14°C.

**New low-energy** integral cross-ventilation system to optimize water chilling efficiency.

**Choice of fingertip control** for fast glass filling (lever down) or bottle filling (lever up).

**Low-energy lights** signal when chilled water is ready, or filter change is due.

**Hidden light sensor** sends appliance to sleep to conserve energy whenever the room goes dark.

**Sleeps or powers OFF** after 2 hours of non-use.

**Plus inbuilt 24/7 on/off timing** allowing power to be turned off for weekday or weekend periods.

**Zip 0.2 micron filter** puts crystal-clear, better-tasting water on tap, filtering out chlorine taste and odour, lead, and impurities as tiny as one five-thousandth of a millimetre, including protozoan cysts such as Cryptosporidium. Also reduces accumulation of mineral scale in boiling water appliances, but does not remove beneficial fluoride.

**Zip HydroTap Commercial models with new Zip G4 power-saving technology.**

| Order Code (a) | Zip Model | Boiling Cups/hr | Rating (kW) @ 230 V | Cabinet Dimensions W x D x H (mm) |
|----------------|-----------|-----------------|---------------------|-----------------------------------|
| HT1710         | C 125 G4  | 125             | 0.2                 | 280 x 476 x 333                   |
| HT1711         | C 175 G4  | 175             | 0.25                | 280 x 476 x 333                   |

Standard Cup = 167 mL.

(a) Order codes shown here are for boiling/ambient tap installed on a sink. To install boiling/ambient tap on a 'font' also specify a font kit: order code 90915.

**A. Location**

Tap must be positioned so that it drains into a suitable sink, or be installed on the optional "tap font kit" which is plumbed to waste. Tap should be situated as closely as possible to directly above the under-sink Command Centre. Maximum distance from the base of the tap to the Command Centre is one metre. Command Centre must have clearances as shown on the drawings. Ventilation accessories (supplied) must be installed as per instructions.

**B. Plumbing**

Must be installed in accordance with AS/NZS3500 plumbing regulations. Designed for direct connection to a potable (drinkable) cold water supply with minimum pressure of 172 kPa. A 500 kPa pressure limiting valve is fitted internally. An isolating valve should be fixed between the water supply and the under-bench Command Centre.

**C. Electrical**

These models are designed to be connected to a 10 amp GPO, 240-230 Volt AC power supply in accordance with AS/NZS 3350 and 3000 wiring regulations.

**Caution**

In some hard water areas where mineral scale accumulation can become a problem, consideration should be given to the maintenance required.

**Five Year Warranty**

Appliance warranty 36 months, plus additional 24 months tank warranty. See website for details.



**Accessories**

- 90915 – Zip G4 font installation kit
- 91290 – Zip 0.2 micron replacement filter

**Technical Assistance**

Zip Heaters (Aust) Pty Ltd  
67-77 Allingham Street  
Condell Park NSW 2200  
Free Call 1800 638 622  
www.zipindustries.com

