





Minimal underbench footprint

All Chill models are extremely compact and are considered to be amongst the smallest under counter chilled water dispensers of their kind.

Chilled water capacity

The Chill units may be small in stature and hidden from view, but are not lacking in chilled water capacity. The Chill range has the capacity to produce from 10 L/hr up to 20 L/hr of high quality chilled drinking water.

Flexible options

The Chill range offers chilled, ambient and sparkling drinking water options as well as adjustable temperature control and a range of tap designs and spout heights, with the appliance concealed under the bench for maximum space efficiency.

Safety first

Total hygiene is a priority and, for this reason, only certified food contact materials are used for all components in contact with liquid and great care is taken in assembling each product. This eliminates the risk of contamination and allows for easy cleaning and maintenance.

Durable design

The compact size of the Chill range does not compromise on strength with a sturdy stainless steel external construction and design for peak ongoing performance and durability.

Instant chilling

The High Performance Direct Chill (CH240) cooling technology delivers maximum performance, hygiene and energy efficiency. It is fully operational within three minutes, providing instant chilling with no possibility of stagnation.





CHILL CH240



CHILL CH270




CHILL CH80



Aqua-Tech Drinking Water Solutions

ABN: 67 742 281 188 Tel: 07 3394 6555







CHILL CH80

The CHILL CH80 is a discreet, compact unit that has the capacity to produce up to 10 L/hr of quality chilled drinking water.

DELIVERS	Chilled Water (Ambient optional)
CHILLING CAPACITY	10 L/hr
COOLING SYSTEM	Silver Turbo Clean cooling system, provides improved hygiene and energy efficiency
WEIGHT	14 kg gross
SIZE (H X W X D)	355 x 200 x 470mm
REQUIREMENTS	power, water

- ✓ Vented faucet
- Powerful refrigeration compressor
- ✓ Simple Installation
- ✓ Stainless steel construction
- ✓ Adjustable temperature control
- External Advanced
 3 stage filtration systems

Optional

- ✓ Font mount
- ✓ 2 way tap for ambient

CHILL CH270

The Chill CH270 has the capacity to provide chilled and sparkling quality water at up to 16 L/hr. The product is supplied with a special elegant two way tap.

DELIVERS	Chilled, Ambient, Sparkling Water
CHILLING CAPACITY	16 L/hr
COOLING SYSTEM	Silver Turbo Clean cooling system, provides improved hygiene and energy efficiency
WEIGHT	25 kg gross
SIZE (H X W X D)	425 x 245 x 400mm
REQUIREMENTS	power, water, CO ²

- ✓ Two way dispenser tap included
- Separate CO2 canister stored externally
- Stainless steel construction
- ✓ Adjustable temperature control
- External Advanced
 3 Stage filtration systems

Optiona

- ✓ Column 3 way tap for ambient water also
- ✓ Font mount

CHILL CH240

The CHILL CH240 delivers quality chilled water via a high performance instant chilling system, with a chilling capacity of up to 20 L/hr.

DELIVERS	Chilled Water (Ambient optional)
CHILLING CAPACITY	20 L/hr
COOLING SYSTEM	High Performance Direct Chill (HPDC) cooling technology for maximum performance, hygiene and energy efficiency
WEIGHT	18 kg gross
SIZE (H X W X D)	425 x 240 x 450mm
REQUIREMENTS	power, water

- ✓ Vented faucet
- Instant chilling system for continuous delivery
- Operates effectively in high temperatures
- ✓ Fully operational within 3 mins of turning on
- Instant chilling, no possibility of stagnation
- ✓ Stainless steel construction
- Adjustable temperature control
- ✓ External Advanced3 Stage filtration systems

Optional

- ✓ Font mount
- ✓ 2 way tap for ambient







ABN: 67 742 281 188 Tel: 07 3394 6555

E: sales@aqua-tech.net.au E: www: aqua-tech.net.au Please note that Aqua-Tech reserves the right to change any information contained in this document without prior notice. Ref: AB112019

